

VERTICAL PLATFORM LIFT

UNA PORTE

COMPACT
MULTITALENT
FOR EASY RETROFITTING

ascendor[®]
LIFTTECHNIK





UNAPORTE

ADVANTAGES & TECHNICAL DATA

- ✓ for indoor and outdoor use
- ✓ soft start/soft stop via a frequency-controlled drive system
- ✓ perfect ratio of space requirement to usable platform area
- ✓ no pit required due to self-aligning drive-on ramp
- ✓ simple retrofitting

CONTROL & OPERATION

- ↑ push-button operation on the platform / remote controlled buttons for landing call stations
- ↑ full graphic color display
- ↑ integrated fault memory
- ↑ numerous adjustment parameters
- ↑ electrical emergency lowering

POWER SUPPLY

- ↑ 220-240V, 1 phase, 10A

FLOOR

- ↑ anodised aluminium tear plate

OPTIONS

- ↑ voice output
- ↑ 2 way voice communication
- ↑ automatic door operators
- ↑ LED RGB lighting
- ↑ automatic emergency power supply
- ↑ SMS remote query of operating states



**FAST
ASSEMBLY**



TRAVEL HEIGHT

- ↑ from 600mm to 3000mm

STOPS

- ↑ 2 stops

DRIVING SPEED

- ↑ 0,15 m/s

LOAD CAPACITY

- ↑ 385 kg

COLOR

- ↑ open platform standard gray metallic
- ↑ lifting column anodised aluminium

PLATFORM SIZE

- ↑ 1400 x 1100 mm (LxB)

REQUIRED SPACE

- ↑ 1690 x 1333 mm (LxB)
with closed swing door

DOOR

- ↑ 930 mm passage width

TYPE OF DRIVE

- ↑ guide chain system with electric drive 0.75 kW
- ↑ safety gear with integrated speed limiter